



maniscalco

australian for mosaics

Installation System Guide

Selection Legend

MANISCALCO PRODUCT CODES		SUBSTRATE CODES	
A:	Mesh mounted Stone	1:	Plywood (interior, dry areas only)
B:	Mesh mounted Pebbles	2:	Concrete
C:	Foil back Glass	3:	Cementitious Board
D:	Crystal Glass	4:	Gypsum wallboard (interior, dry areas only)
E:	Translucent Glass	5:	Ceramic Tile
F:	Stainless Steel Mosaics		
G:	Sydney Harbor resin		
H:	Aluminum Mosaics		
I:	Metal, glass, stone mix		

Adhesives

BOSTIK ADHESIVE	DESCRIPTION	SUBSTRATE	MANISCALCO PRODUCT
Bostik PM Thinset gray	multi-purpose polymer-modified	1,2,3,4,5	A,B,F,G,H
SINGLE-FLEX Thinset gray	premium polymer-modified	1,2,3,4,5	A,B,F,G,H
STONEWALL Thinset white	high-performance polymer-modified, non-sag	1,2,3,4,5	A,B,C,D,E,F,G,H,I
GLASSMATE Thinset white	bright white polymer-modified, non-sag	1,2,3,4,5	A,B,C,D,E,F,G,H,I

Grouts

BOSTIK GROUT	MANISCALCO PRODUCT.
Dry Tile Unsanded Grout	A,B,C,D,E,F,G,H,I
Ceramic Tile Sanded Grout	A,B
TruColor Premixed Urethane Grout	A,B,C,D,E,F,G,H,I
1900 Epoxy Modified Grout & Mortar Admix	A*,B* (*except when installing moisture sensitive stones)
Dimension Reflective Urethane Grout	A,B,C,D,E,F*,G*,H*,I* (*pay special attention to Technical Data Sheet)

Notes

- **Disclaimer:** This document is meant to be a product and substrate recommendations guide. It is not meant to replace Maniscalco or Bostik product installation guides or Technical Data Sheets.
- For specific substrate or unlisted specification requirements please contact us on techinfo@maniscalcostone.com and in conjunction with Bostik we will provide a tailor-made solution.
- Please visit <http://www.maniscalcostone.com/Instructions.aspx> or <http://bostik.scangroup.net> (search for “ceramic” or specific products) for further details.

