KOSMOS PRODUCT SPECIFICATION

GLAZED FLOOR TILE 60 X 60cm

Pressed Ceramic Tiles International Norms ISO 13006-10545/98 GROUP: B1b

No.	Icon	Test item	Unit	Requirements of Standard		Test	Result
1	+	Dimensional variation	(%)	length of side	0.6	< 0.6	Qualified
2		Side straightness	(%)	± 0.5		< 0.5	Qualified
3		Squareness	(%)	± 0.6		< 0.6	Qualified
4	† †	Surface flatness	(%)	Center curvature degree	± 0.5	< 0.5	Qualified
				Warping degree	± 0.5	< 0.5	Qualified
				Side curvature degree	± 0.5	< 0.5	Qualified
5	Q	Surface quality		Sighting vertically at a distance of 0.8 meter away from the tile no defect on surface is observed in at least 95% of the tile		conformed	Qualified
6	6	Water absorption	(%)	Average value ≤ 3 individual ≤ 3.3		< 3.0 < 3.0	Qualified
7		Breaking strength	N	When thickness ≥ 7.5mm the Average value ≥ 1100		> 1100	Qualified
8	₹	Rupture modulus	Мра	Average value ≥ 30 individual ≥ 27		> 30 > 27	Qualified
9	3	Abrasion resistance	mm ³	< 175		< 175	Qualified Class 4
10	₩	Scratch resistance	МОН	_		>6	Qualified
11	**	Frost resistance		No cracking after test		conformed	Qualified
12	4	Resistance to acids & alkalis		not less than grade GB		Grade GA	Qualified
13		Chemical resistance		not less than grade GB		Grade GA	Qualified
14	1	Slip resistance	R DCoF	Slip rating test DCoF: 0.42		R11 > 0.42	Qualified

KOSMOS




Italian ink-jet design Gres Porcelain Floor Tiles





KOSMOS











Dark Grey

Available Finishes: Matte / Lapatto / Exterior

Packaging:

 24 x 24"
 4 pcs. / ctn.
 15.5 sqft / ctn.
 66.14 lbs. / ctn.

 12 x 24"
 8 pcs. / ctn.
 15.5 sqft / ctn.
 66.14 lbs. / ctn.

 24 x 48"
 2 pcs. / ctn.
 15.5 sqft / ctn.
 66.14 lbs. / ctn.

 18 x 36"
 4 pcs. / ctn.
 17.44 sqft / ctn.
 81.57 lbs. / ctn.

620 sqft / pallet 3' 6" pallet: 40 ctn. / pallet 620 sqft / pallet 3' 6" pallet: 40 ctn. / pallet 620 sqft / pallet 3' 6" pallet: 40 ctn. / pallet 837 sqft / pallet 3' 6" pallet: 40 ctn. / pallet



*Sizes are nominal