SLATE PRODUCT SPECIFICATION

GLAZED FLOOR TILE 60x60cm

Pressed Ceramic Tiles International Norms ISO 13006-10545/98 GROUP: B1b

No.	Icon	Test item	Unit	Requirements of Standard		Test result	Result
1	+	Dimensional variation	(%)	length of side	0.6	< 0.6	Qualified
2	₩	Side straightness	(%)	± 0.5		< 0.5	Qualified
3		Squareness	(%)	± 0.6		< 0.5	Qualified
4	<u>+</u> +	Surface flatness	(%)	Center curvature degree	± 0.5	< 0.5	Qualified
				Warping degree	± 0.5	< 0.5	Qualified
				Side curvature degree	± 0.5	- 0.1	Qualified
5	Q	Surface quality		Sighting vertically at a distance of 0.8 meter away from the tile no defect on surface is observed in at least 95% of the tile		conformed	Qualified
6	•	Water absorption	(%)	Average value ≤ 3 individual ≤ 3.3		< 0.28 < 0.30	Qualified
7		Breaking strength	N	When thickness ≥ 7.5mm the Average value ≥ 700		< 750	Qualified
8	[Rupture modulus	Мра	Average value ≥ 30 individual ≥ 27		> 35 > 32	Qualified
9		Abrasion resistance	revs	1700		>1700	Qualified Class 4
10	***	Scratch resistance	МОН	_		> 6	Qualified
11	〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇	Frost resistance		No cracking after test		conformed	Qualified
12	4	Resistance to acids & alkalis		not less than grade GB		Grade GA	Qualified
13		Chemical resistance		not less than grade GB		Grade GA	Qualified
14	1	Slip resistance	R DCoF	Ramp slip rating test DCoF: 0.42		R11 > 0.42	Qualified

SLATE



Italian ink-jet design Exterior floor tiles





SLATE





Δn

Finishes Available : Matte / Exterior Finish

Packaging:

*24 x 24" 4pcs. / ctn. 15.5 sqft / ctn. 66.14 lbs. / ctn. 3' 6" pallet: 40ctn. / pallet 620 sqft / pallet *12 x 24" 8pcs. / ctn. 15.5 sqft / ctn. 66.14 lbs. / ctn. 3' 6" pallet: 40ctn. / pallet 620 sqft / pallet

*Sizes are nominal

