

Alhambra Series

Deco Tiles



maniscalco

The Alhambra Deco Tiles are expertly crafted to harmonize flawlessly with the aesthetic of the wall tile offering. With two unique designs, these floor patterns provide flexible coordination with any of the four color mixes available in this series. Whether choosing a vibrant or understated palette, these tiles effortlessly elevate the ambiance, infusing a touch of Spanish charm into your design scheme.



Layla

Layla



Product Sku: AL8X8LY
Color: Layla
Graphic Faces: 20
Sample Card Sku: MSC910-021

Floor + Wall



Layla

Alhambra Series

Deco Tiles



maniscalco




Yasmina



Product Sku: AL810YA
Color: Yasmina
Graphic Faces: 6+
Sample Card Sku: MSC910-021



Tessina



Product Sku: AL8X8TE
Color: Tessina
Graphic Faces: 6+
Sample Card Sku: MSC910-020

Alhambra Series

Deco Tiles



Technical Data (Deco Tiles):

| Standard Norms | Characteristic | Average Values of Production |
|-------------------------|--------------------------------|------------------------------|
| EN-ISO 10545-2 | Dimensional Features | Accomplish/Conform |
| EN-ISO 10545-3 | Water Absorption | > 0.5% |
| EN-ISO 10545-4 | Bending strength | > 35 N/mm ² |
| | Breaking strength | > 1300 N |
| EN ISO 10545-7 | Resistance to surface abrasion | Class 4 |
| EN-ISO-10545-9 | Thermal shock resistance | Accomplish/Conform |
| EN ISO 10545-11 | Crazing resistance | Accomplish/Conform |
| EN ISO 10545-12 | Frost resistance | Accomplish/Conform |
| EN ISO 10545-13 | Chemical resistance | GHA |
| EN ISO 10545-14 | Resistance to stains | 5 |
| UNE-EN-13501-1 | Resistance to fire | A1-A1 FL |
| Friction Coefficient- | | |
| UNE-EN 16165:2022 (C,A) | Pendulum | C3 |
| UNE-EN 16165:2022 (B) | Inclined Platform | R10 |
| ANSI A326.3:2021 | DCOF | > 0.42 |
| BS-EN- 16165:2021 (C) | PTV | 36+ |

Usage (Deco Tiles):

| Material | Interior Residential Wall | Interior Residential Floor | Backsplash | Shower Wall | Shower Floor | Fireplace Surround | Exterior Wall | Exterior Floor | Pool | Sealing Required | Color Variation |
|-----------|---------------------------|----------------------------|------------|-------------|--------------|--------------------|---------------|----------------|------|------------------|-----------------|
| Porcelain | YES | YES | YES | YES | YES | YES | YES | YES | YES | NO | V2 |

Packaging:

| PC Size | Sold By | SF Per CTN | PC Per CTN | Weight Per Ctn | Ctn Per Pallet |
|----------|---------|------------|------------|----------------|----------------|
| 8" x 8" | CTN | 5.60 | 13 | 24.00 lb. | 87 |
| 8" x 10" | CTN | 5.60 | 13 | 26.00 lb. | 96 |

Alhambra Series

Undulated Wall Tiles



Introducing Alhambra Series, a captivating collection that redefines elegance in tile design. The undulated wall tiles, each measuring 2-1/2" x 8", present an aesthetic that blends tradition with contemporary sophistication. The series includes a palette of four distinct shades, shaped by our best-selling tile colors. These ink jet printed colors, are meticulously crafted to inspire the allure of the zellige color style. Each variation characterized by a smooth, matte finish that exudes timeless charm. Matching bullnose options are available in the dimensions of 1" x 12". This ensures a cohesive look, providing a finishing touch that complements the overall design scheme.



Café Mix

Café Mix



Product Sku: AL28CA

Graphic Faces: 6

Sample Card Sku: MSC910-002



Bullnose Sku: AL112CA

Menta Mix



Product Sku: AL28ME

Graphic Faces: 8

Sample Card Sku: MSC910-003



Bullnose Sku: AL112ME



Menta Mix


Alhambra Series

Undulated Wall Tiles



maniscalco

Lago Mix



Product Sku: AL28LA
Graphic Faces: 7
Sample Card Sku: MSC910-004



Bullnose Sku: AL112LA



Crema Mix



Crema Mix



Product Sku: AL28CR
Graphic Faces: 6
Sample Card Sku: MSC910-001



Bullnose Sku: AL112CR

Alhambra Series

Undulated Wall Tiles



Technical Data (Undulated Tiles):

| Standard Norms | Characteristic | Average Values of Production |
|---------------------|--|--|
| UNE-EN-ISO 10545-2 | Length & Width | + 0.2% |
| | Thickness | + 5.6% |
| | Surface quality | 99% of the tiles are free from visible defects |
| UNE-EN-ISO 10545-3 | Water Absorption | Group Bill > 10% |
| UNE-EN-ISO 10545-4 | Breaking load | 345 N |
| | Modulus of rupture | 14 N / mm ² |
| | Breaking strength | 638 N |
| EN 101: 1991 | Scratch hardness of surface according Mohs | Class 4 (12000 rev) |
| UNE-EN ISO 10545-7 | Resistance to surface abrasion for glazed tiles . PEI method | Class 4 (12000 rev) |
| UNE-EN ISO 10545-11 | Cracking resistance | Resistant. (Tiles tested are free from crazes on the glazed surface) |
| UNE-EN ISO 10545-13 | Resistance to low concentrations of acids and alkalis | GLA Non-visible effects |
| | Resistance to high concentrations of acids and alkalis | GHA Non-visible effects |
| | Resistance to domestic products and swimming pool salts | GLA Non-visible effects |
| UNE-EN ISO 10545-14 | Resistance to stains | Class 5 |

Usage (Undulated Tiles):

| Material | Interior Residential Wall | Interior Residential Floor | Backsplash | Shower Wall | Shower Floor | Fireplace Surround | Exterior Wall | Exterior Floor | Pool | Sealing Required | Color Variation |
|----------|---------------------------|----------------------------|------------|-------------|--------------|--------------------|---------------|----------------|------|------------------|-----------------|
| Ceramic | YES | NO | YES | YES | NO | YES | NO | NO | NO | NO | V3 |

Packaging (Undulated Tiles):

| PC Size | Sold By | SF Per CTN | PC Per CTN | Weight Per Ctn | Ctn Per Pallet |
|---------------------|---------|------------|------------|----------------|----------------|
| 2-1/2" x 8" | CTN | 5.6 | 40 | 18.00 lb. | 150 |
| 1" x 12" (Bullnose) | PC | N/A | 57 | 14.50 lb. | N/A |